

Office Action Response
Serial No. 09/273,948
Page 3

IN THE CLAIMS

Please consider the claims as follows:

1. (Previously Presented) A data network comprising
a source that transmits data messages to a plurality of receivers, said receivers forming a multicast group, and wherein each of said plurality of receivers comprises
a first apparatus that receives transmissions of data messages from the source to each of said plurality of receivers and accumulates statistics relating to said transmissions of data messages from the source to said receiver,
a second apparatus that computes a congestion control value and sends the value to the source, and wherein the source adjusts its transmission of data packets to the receivers as a function of a selected one or more of a plurality of congestion control values that it receives from respective ones of the receivers,
wherein the receivers forming the multicast group also form a multilevel hierarchical reporting network that forwards a congestion control value to the source, wherein a receiver positioned at each level in said multilevel hierarchical reporting network includes apparatus that computes a new consolidated congestion control value, said new consolidated congestion control value being a function of the congestion control value that said receiver locally generates and a consolidated congestion control value that said receiver receives from receivers positioned at a preceding level in said multilevel hierarchical reporting network, and said receiver then forwarding said new consolidated congestion control value to the source via the next succeeding level in the multilevel hierarchical reporting network.
2. (Canceled)
3. (Previously Presented) The data network of claim 1 wherein the source is positioned at the highest level in the reporting hierarchy.
4. (Original) The data network of claim 1 wherein each of the receivers uses a

Office Action Response
Serial No. 09/273,948
Page 4

window based scheme to determine a maximum expected sequence number as its respective congestion control value, and wherein the source uses the minimum of the congestion control values that it respectively receives from the receivers as a maximum sequence number of a next packet that the source transmits to the receivers.

5. (Previously Presented) The data network of claim 1 wherein each of the receivers uses a window based scheme to determine, as a function of an updated window size, maximum sequence number of packets contiguously received, total length of received packets that are not contiguous and size of an associated reassembly buffer a maximum expected sequence number as its respective congestion control value, and wherein the source uses the minimum of the congestion control values that it respectively receives from the receivers as a maximum sequence number of a next packet that the source transmits to the receivers.

6. (Original) The data network of claim 4 wherein the second apparatus includes apparatus that determines a transmission window as a function of loss and delay measured by the respective receiver, and generates the respective congestion control value as a function of (a) the determined transmission window and (b) sequence number of the last data packet received successfully in sequence with prior received data packets.

7. (Original) The data network of claim 4 wherein the second apparatus includes apparatus that determines a transmission window as a function of loss and delay measured by the respective receiver and generates its respective congestion control value as (a) a function of the determined transmission window, (b) sequence number of a last data packet received successfully in sequence with prior received data packets and (c) number of data packets received out of sequence.

8. (Original) The data network of claim 4 wherein each receiver includes a buffer for storing received data messages and wherein the second apparatus includes

Office Action Response
Serial No. 09/273,948
Page 5

apparatus that determines a transmission window as a function of loss and delay measured by the respective receiver and generates its respective congestion control value as (a) a function of the sequence number of a last data packet received successfully in sequence with prior received data packets and minimum of (bi) the transmission window plus the number of data packets received out of sequence, or (b2) the number of memory locations in the reassembly buffer available for the storage of out-of-sequence data packets.

9. (Original) The data network of claim 3 wherein each of the receivers uses a rate based scheme to determine its respective congestion control value, and wherein the source applies the minimum of the of the congestion control values that it respectively receives from the receivers as a rate of transmission of new data packets.

10. (Previously Presented) The data network of 1 wherein the source inserts a time stamp in a data packet that it transmits to the multicast group of receivers and wherein the first apparatus associates a received data packet with a current time stamp and wherein said first apparatus includes apparatus that determines a trip delay from the source to each of said plurality of receivers as a function of the difference of the inserted time stamp and a current time stamp.

11. (Previously Presented) The data network of claim 1 wherein each receiver further includes third apparatus that determines a trip delay to the source via the reporting network as a function of a (a) time stamp that it associates with a message containing a congestion control value that the receiver forwards to a receiver positioned at the next highest level in the reporting hierarchy, and (b) trip delay returned by the receiver positioned at the next highest level, in which the returned trip delay is indicative of the trip delay from the latter receiver to the source.

12. (Previously Presented) The data network of claim 11 wherein each of the receivers forward its respective congestion control value to the source via the IP layer

Office Action Response
Serial No. 09/273,948
Page 6

multicast network.

13. (Canceled)

14 (Canceled)

15. (Currently Amended) A data receiver, comprising:

first apparatus that receives a data packet from a source of data packets and accumulates particular information relating to the transmission of data packets toward a receiver via a data network; and

second apparatus that generates a transmission control value as a function of the accumulated information and forwards the generated value as a feedback message toward the source, said feedback message adapted to enable the source to control its transmission of data messages as a function of (a) the transmission control value received from the receiver and (b) transmission control values received by the receiver from other such receivers, wherein said data receiver is one of a plurality of receivers that form a multicast group within the data network. ~~The receiver of claim 14~~ wherein the multicast group of receivers form a multilevel hierarchical reporting network that forwards a transmission congestion control value toward the source and wherein a receiver positioned at an intermediate level in the reporting hierarchy includes apparatus that generates a consolidated congestion control value as a function of a combination of the congestion control value that it generates locally and each consolidated congestion control value that it receives from receivers positioned at the preceding level in the hierarchy and then forwards the consolidated congestion control value to the source via the next succeeding level in the reporting network.

16. (Currently Amended) A data receiver, comprising:

first apparatus that receives a data packet from a source of data packets and accumulates particular information relating to the transmission of data packets toward a receiver via a data network; and

Office Action Response
Serial No. 09/273,948
Page 7

second apparatus that generates a transmission control value as a function of the accumulated information and forwards the generated value as a feedback message toward the source, said feedback message adapted to enable the source to control its transmission of data messages as a function of (a) the transmission control value received from the receiver and (b) transmission control values received by the receiver from other such receivers. The data receiver of claim 13 wherein said data receiver uses a window based scheme to determine a maximum expected sequence number as its respective congestion control value, and wherein the source uses the minimum of the congestion control values that it receives as a maximum sequence number of a next packet that the source transmits to each said receiver.

17.(Original) The receiver of claim 15 wherein the second apparatus includes apparatus that determines a transmission window as a function of loss and delay measured by the respective receiver and generates its respective congestion control value as a function of the determined transmission window and sequence number of the last data packet received successfully in sequence with prior received data packets.

18.(Original) The receiver of claim 15 wherein each of the receivers uses a window based scheme to determine, as a function of an updated widow size, maximum sequence number of packets contiguously received, total length of received packets that are not contiguous and size of an associated reassembly buffer a maximum expected sequence number as its respective congestion control value, and wherein the source uses the minimum of the congestion control values that it respectively receives from the receivers as a maximum sequence number of a next packet that the source transmits to the receivers.

19.(Original) The receiver of claim 15 wherein the second apparatus includes apparatus that determines a transmission window as a function of loss and delay measured by the respective receiver and generates its respective congestion control value as a (a) function of the determined transmission window, sequence number of the

Office Action Response
Serial No. 09/273,948
Page 8

last data packet received successfully in sequence with prior received data packets and
(b) number of data packets received out of sequence.

20. (Currently Amended) A data receiver comprising
first apparatus that receives a data packet from a source of data packets and
accumulates particular information relating to the transmission of data packets toward a
receiver via a data network; and
second apparatus that generates a transmission control value as a function of
the accumulated information and forwards the generated value as a feedback message
toward the source, said feedback message adapted to enable the source to control its
transmission of data messages as a function of (a) the transmission control value
received from the receiver and (b) transmission control values received by the receiver
from other such receivers. The receiver of claim 13 wherein each receiver further
comprises a re-assembly buffer for storing received data packets and wherein the
second apparatus includes apparatus that determines a congestion control value as a
function of function of loss and delay measured by the respective receiver; and
generates its respective congestion control value as a (a) function of the
sequence number of a last data packet received successfully in sequence with prior
received data packets and minimum of (b) a transmission window plus the number of
data messages received out of sequence, and (b2) the number of memory locations in
the re-assembly buffer available for the storage of out-of-sequence data packets.

21. (Currently Amended) A data receiver comprising
first apparatus that receives a data packet from a source of data packets and
accumulates particular information relating to the transmission of data packets toward a
receiver via a data network; and
second apparatus that generates a transmission control value as a function of
the accumulated information and forwards the generated value as a feedback message
toward the source, said feedback message adapted to enable the source to control its
transmission of data messages as a function of (a) the transmission control value

Office Action Response
Serial No. 09/273,948
Page 9

received from the receiver and (b) transmission control values received by the receiver from other such receivers. ~~The receiver of claim 13~~ wherein the receiver uses a rate based scheme to determine the congestion control value, and wherein the source applies the minimum of the congestion control values that it receives as a rate of transmission of new data packets.

22. (Currently Amended) The receiver of claim 21 wherein said data receiver is one of a plurality of receivers that form a multicast group within the data network,¹⁴ wherein the source inserts a time stamp in a data packet that it transmits to the multicast group of receivers and wherein the first apparatus associates a received data packet with a current time stamp and wherein said first apparatus includes apparatus that determines a trip delay from the source to the receiver as a function of the difference of the inserted time stamp and current time stamp.

23. (Currently Amended) The receiver of ~~The receiver of claim 21 wherein said data receiver is one of a plurality of receivers that form a multicast group within the data network,~~¹⁴ wherein each receiver further includes third apparatus that determines a trip delay to the source via the reporting network as a function of a (a) time stamp that it associates with a message containing a congestion control value that the receiver forwards to a receiver positioned at the next highest level in the reporting hierarchy, and (b) trip delay returned by the receiver positioned at the next highest level, in which the returned trip delay is indicative of the trip delay from the latter receiver to the source.

24. (Canceled)